



Speaker Cable Pro 2C & 4C



Construction

Material	Solid Bare Copper
Construction	0.25±0.008×30
Stranded Dia.(mm)	1.58

Insulation

	2 Core	4 Core
Material	LSZH	LSZH
Thickness	0.31	0.34
Insulation Dia.(mm)	2.25±0.1 x 2C	2.25±0.1 x 4C
Insulation Color	Red, Black	Red, Black, White, Green
Filler	Cotton Rope	None

Jacket

	LSZH	LSZH
Nom.Thickness(mm)	0.60	0.80
Dia.(+/-0.15mm)	6.20±0.20	7.50±0.20
Jacket Color	Pink(RAL-3015)	Pink(RAL-3015)

Marking (Black Ink)

2 Core	S152L 2c x 1.5mm ² Speaker LSZH - Order No	+001m.....+100m
4 Core	S154L 4c x 1.5mm ² Speaker LSZH - Order No	+001m.....+100m

Electrical Characteristics

Max.Conductor DC Resistance at 20°C (Ω/Km)	12.6
Rated Temperature(°C)	80
Operating Voltage U ₀ /U (V)	450/750
Min.Insulation DC Resistance at 20°C (MΩ*KM)	200
Test Voltage (V)	3000
Minimum bending radius	10x OD cable